

HIP[®]

Highest Ideas Products

SWING GATE

ระบบประตูกันทางเดิน

C Series



Ø168x600x1050mm
Material Satin Stainless Steel 304
two way swing
automatically

SWING GATE C SERIES

Model: **CMC401**

Features:

- 1) with zero self-test function, user maintenance and use
- 2) illegal entry with alarm functions.
- 3) erosion control features, the gate signal is not received, the arm automatically locked.
- 4) IR / mechanical double anti-pinch function, in the arm meet resistance during reset, the specified time automatically stops the motor, and the intensity is very small, while giving an alarm.
- 5) with automatic reset function, pedestrians card valid, if the system does not pass within the specified time, the system will automatically cancel the pedestrian access permissions.
- 6) standard external communication interface with a variety of card readers attached, and through management computer remote control and management.

Technical parameters:

Power supply:	AC220V +- 10% V 50 +- 10% HZ .
Input Interface:	12V level signal or pulse width > 100ms of 12V pulse signal, the drive current > 10mA .
Communication Interface:	RS232 serial interface.
Drive motor:	DC24V motor.
Traffic Direction:	one-way or two-way traffic.
IP protection class:	42 .
Relative humidity:	<= 90% , non-condensing.
Open, closing time:	1 sec.
Power system start-up time:	3 seconds.
passage persons:	40 people / minute.
normal life:	400 million times.
Chassis Material:	Domestic standard 304 stainless steel. Thickness: GB 1.2mm ~ 1.5mm .
Net channel width sizes: single use:	the standard channel width 550mm , follo use: 1100 mm ~ 1600 mm .
Chassis appearance may request.	



Extensions:

- through the onboard buttons, programmable device working condition.
- motherboard counting function.
- powerful voice prompts.